

Application Instructions

There are three (3) layers to the Words™ sheet:

- The top layer is the translucent transfer sheet
- The middle layer is the vinyl lettering
- The bottom layer is the white backing paper

1. Start with a clean, dry, dust-free surface. If desired surface is freshly painted, it is advisable to wait 30 days before applying.

2. Remove vinyl lettering sheet(s) from box and unroll on a hard, flat surface with white backing paper on the bottom and the transfer sheet on top. Rub application tool over the entire sheet to ensure the lettering adheres to top transfer sheet.

3. Determine layout of letters on the wall. Words can be cut apart and applied stacked, on angles or around window and door mouldings. Choose your location and layout carefully as the vinyl may be removed after application, but not re-applied. Be creative, have fun!



4. Once desired layout is decided, use a tape measure and ruler as a straight edge to create faint pencil line(s) on the wall with which to align the bottom edge of the transfer sheet for the application process.



5. Place the lettering sheets in desired position on wall. With masking tape, secure sheets along the top edge, making sure you have lined up the bottom of the transfer sheet with the pencil lines.



6. Once lettering sheets are taped into position, flip sheets up and slowly and carefully peel white backing paper away from lettering and top transfer sheet. Once removed, carefully flip back down and lay top transfer sheet onto wall.



7. Using enclosed application tool, thoroughly rub over vinyl letters to remove air bubbles and ensure lettering transfers from transfer sheet and securely adhere to wall surface.



8. Slowly and carefully remove top transfer masking sheet by pulling back one top corner. Continue pulling back entire sheet making sure letters adhere to applied surface. Once sheet is removed, rub letters down with your fingers.



Lettering can be applied to most non-porous, smooth, or semi-smooth surfaces. Porous or heavily textured surfaces are not recommended. We cannot guarantee lettering will adhere to all surfaces. Lot 26 Studio, Inc. is not responsible for any damages resulting from the use of, or inability to use this product. Vinyl lettering can be easily removed by carefully heating it up with a hand-held hair dryer, on a low setting, and peeling it away from the wall.